

2 1	
DESCRIPTION	]
LVE, GAS, 316SS	
GAS, 10–180 SCFH / 85 LPM	F
, GAS, 316SS	
WITCH, WATER, @ 5 PSI/0.34BAR AUGE, GAS, 0-160PSI/0-12BAR, 300SERIES STAINLESS	-
AUGE, WATER, 0-60PSI/0-4BAR, 300SERIES STAINLESS	L
TERFLY VALVE, LUG, LEVER HANDLE, LOCKING	
DINT OF CONNECTION	
GREY, SCH80, PVC	
VIRING, REF. ELECTRICAL SCHEMATIC	
6mm, PTFE	E
G, 6mm, PTFE	
FLANGE, SCH80, 8HOLES, PVC	

D

С

В



## DISCHARGE CONNECTION ISO FLANGE, PN10, D110mm

ALLOW 3FT (1METER) EASEMENT AROUND THE EQUIPMENT
SEE MANUAL FOR GAS SUPPLY PRESSURE ADJUSTMENT INSTRUCTIONS
WATER TEMPERATURE 40°F-140°F (4°C- 60°C)
REFER TO INSTALLATION MANUAL FOR RECOMMENDED LOCATION

′03/23	20800 BELSHAW AVENUE CARSON CA, 90746	
23/23	DRAWING TITLE: TRINITY L1, METRIC, P&ID	
24/23	DRAWING NO: 50F0-400	A
mm]. [ <u>+</u> 6.35] CIFIED	⊕ € SIZE: B SCALE: 1:1 SHEET: 1/1 REV: A	
1	2 1	_